

## Pool Basic

The SEKO Group has developed new robust and reliable systems, that consist of a small enclosure supporting dosing pumps and control instruments. These systems are well integrated between control of pH/Redox and easy management.



- Flow rate • 1.5 l/h or 5 l/h
- Back pressure 1.5 bar
- pH scale • 6.2...8.0
- Automatic electrode calibration with quality indication

### Pool Basic pH



- Flow ate • 1.5 l/h or 5 l/h
- Back pressure 1.5 bar
- Redox scale 660...840mV
- For Redox potential lower than 660 mV use Pool Plus series
- Automatic electrode calibration with quality indication

### Pool Basic Redox

- IP 55 protection degree enclosure
- Led display
- Prevention from unproper set-point changes
- Electrodes automatic calibration
- Electrodes quality control
- Instant set-point reading
- Programmable dosing time
- Easy and quickly programmable set points
- Peristaltic technology application, with related advantages: low noise, easy to use, light weight, little space needed, low maintenance, no valves, no siphoning effect, prevention from direct contact with chemicals
- Pump on-hold switch and flashing led alarm



- Flow rate • 1.5 l/h or 5 l/h
- Back pressure 1.5 bar
- pH scale • 6.2...8.0
- Redox scale 660...840mV

For Redox potential lower than 660 mV use Pool Plus series

Automatic electrode calibration with quality indication

**Pool Basic  
pH/Redox**

## Accessories

Pool Basic Redox	•	•	•	•	•	•		•
Pool Basic pH	•	•	•	•		•	•	
Pool Basic pH/Redox	•	•	•	•	•	•	•	•

Redox version is also available with electrovalve control to be used with powder or solid chlorine

## OPTIONALS

- Flow control input
- pH temperature compensation input
- Chemical tank level alarm