

## Pool Plus

Once again the SEKO Group has innovated its production with a new range of systems, for swimming pools: the POOL PLUS. This range consists of three different systems, designed taking customers' needs into account, and is able to respond to all pH & Redox controlling conditions.



### Pool Plus

- pH scale • 0...14.00 pH
- Redox scale • 0...1500 mV
- Alarm kit • standard
- Pumps are directly connected to magnetothermal general switch and pump stop switch
- 0/4÷20 mA output for measure trasmission

- Fast and easy mounting
- High resistance plastic enclosure IP 55 protection degree
- Wiring on internal terminal board
- 230 Vac or 115 Vac 50 - 60 Hz power supply
- Pumps on-hold switch
- System ON-OFF switch
- ON-OFF remote switch (only with alarm kit)
- LCD displays
- Orientable pump outlets (for electromagnetic type)
- PH-20 control instrument for pH control
- 0...14,00 ± 0,01 pH
- MV-20 control instrument for Redox (ORP) control
- 0...1500 ± 1 mV
- Multiturn accuracy setting potentiometers
- 2 programmable set points (pump regulation and alarm)
- Output current settable on 0/4...20 mA



**Pool Plus-X**

- pH scale • 0...14.00 pH
- Redox scale • 0...1500 mV
- Manual control instruments calibration
- Electromagnetic pumps
- Pump flow rate • 3 l/h
- Back pressure • 3 bar
- Pumps controlled by level or flux alarm
- Optional Alarm Kit



**Pool Plus-P**

- pH scale • 0...14.00 pH
- Redox scale • 0...1500 mV
- Manual control instruments calibration
- Peristaltic pumps
- Pump flow rate • 5 l/h
- Back pressure • 1.5 bar
- Pumps controlled by level or flux alarm
- Optional Alarm Kit

**Accessories**

<b>Pool Plus P</b>	•	•	•	•	•	•	•	•
<b>Pool Plus X</b>	•	•	•	•	•	•	•	•